



PAR38 Spotlight



FZL-PAR38-02 Series

22W

- Luminous Flux (lm): 1200 (±10%) with 3000K / 1400 (±10%) with 6000K
- Power Consumption (W): 22
- LED: Samsung
- CCT (K): 3000K (WW) / 6000K (CW)
- Lifetime (hrs): >35000
- Beam Angle: Clear Cover – 25° / 40° / 60°
Frosted cover – 120°
- Socket: E26 / E27
- Net Weight (kgs): 0.505 (±10%)
- Switching Dimmable Function
(4 steps: 100%/ 50%/ 25%/ 12%)

Model	FZL-PAR38-02-WW-22 / FZL-PAR38-02-CW-22	FZL-PAR38-02-WW-22SD / FZL-PAR38-02-CW-22SD
Input Voltage (V)	AC 90 – 264V (Non-dimmable)	AC 90 – 264V (Switching Dimmable)
Model	FZL-PAR38-02-WW-22TDH / FZL-PAR38-02-CW-22TDH	FZL-PAR38-02-WW-22TDL / FZL-PAR38-02-CW-22TDL
Input Voltage (V)	AC 220 – 240V (TriAC dimmable)	AC 100 – 120V (TriAC dimmable)

FZL-PAR38-03 Series

22W

- Luminous Flux (lm): 1300 (±10%) with 3000K / 1550 (±10%) with 6000K
- Power Consumption (W): 22
- LED: Cree
- CCT (K): 3000K (WW) / 6000K (CW)
- Lifetime (hrs): >35000
- Beam Angle: Clear Cover – 25° / 40° / 60°
Frosted cover – 120°
- Socket: E26 / E27
- Net Weight (kgs): 0.505 (±10%)
- Switching Dimmable Function
(4 steps: 100%/ 50%/ 25%/ 12%)

Model	FZL-PAR38-03-WW-22 / FZL-PAR38-03-CW-22	FZL-PAR38-03-WW-22SD / FZL-PAR38-03-CW-22SD
Input Voltage (V)	AC 90 – 264V (Non-dimmable)	AC 90 – 264V (Switching Dimmable)
Model	FZL-PAR38-03-WW-22TDH / FZL-PAR38-03-CW-22TDH	FZL-PAR38-03-WW-22TDL / FZL-PAR38-03-CW-22TDL
Input Voltage (V)	AC 220 – 240V (TriAC dimmable)	AC 100 – 120V (TriAC dimmable)