


# FloodLight


## FZL-FL Series

CE FC IP65


[FZL-FL12-00-12]




[FZL-FL35-00-35]



[FZL-FL60-00-60]



[FZL-FL110-00-110]



12W

- Power Consumption (W): 12 (±10%)
- LED: Epistar
- Input Voltage (V): AC 100 - 240V
- Lifetime (hrs): >35000
- Beam Angle: 120°
- IP65
- Net Weight (kgs): 0.50 (±10%)
- Dimmable: Non-dimmable

Model	FZL-FL12-00-WW-12	FZL-FL12-00-CW-12
CCT (K)	3000 (±10%)	6000 (±10%)
Luminous Flux (lm)	700 (±10%)	800 (±10%)

35W

- Power Consumption (W): 37 (±10%)
- LED: Epistar
- Input Voltage (V): AC 100 - 240V
- Lifetime (hrs): >35000
- Beam Angle: 120°
- IP65
- Net Weight (kgs): 2.3 (±10%)
- Dimmable: Non-dimmable

Model	FZL-FL35-00-WW-35	FZL-FL35-00-CW-35
CCT (K)	3000 (±10%)	6000 (±10%)
Luminous Flux (lm)	2200 (±10%)	2700 (±10%)

60W

- Power Consumption (W): 61 (±10%)
- LED: Epistar
- Input Voltage (V): AC 100 - 240V
- Lifetime (hrs): >35000
- Beam Angle: 120°
- IP65
- Net Weight (kgs): 3.5 (±10%)
- Dimmable: Non-dimmable

Model	FZL-FL60-00-WW-60	FZL-FL60-00-CW-60
CCT (K)	3000 (±10%)	6000 (±10%)
Luminous Flux (lm)	3700 (±10%)	4500 (±10%)

110W

- Power Consumption (W): 110 (±10%)
- LED: Epistar
- Input Voltage (V): AC 100 - 240V
- Lifetime (hrs): >35000
- Beam Angle: 120°
- IP65
- Net Weight (kgs): 8.0 (±10%)
- Dimmable: Non-dimmable

Model	FZL-FL110-00-WW-110	FZL-FL110-00-CW-110
CCT (K)	3000 (±10%)	6000 (±10%)
Luminous Flux (lm)	7500 (±10%)	9000 (±10%)